GENIEMAT® FF05NP SOUND CONTROL UNDERLAYMENT



PRODUCT SPECIFICATION

PRODUCT NAME:	GenieMat FF05NP
DESCRIPTION:	Robust reduced sound transmission mat made from 94% recycled rubber content used when superior sound control is required in multifamily housing, high-rises, or commercial buildings.
Features and Benefits:	 Significantly reduces impact sound Mould, bacteria, fungi, and water resistant Qualifies for LEED® points Easy to install and rolls out quickly Will not fail under high point loads CE marked
DIMENSION:	Rollgood: 1.22 m wide, 9.14 m long (4' wide, 30' long)
THICKNESS:	nom. 5 mm (¹³ / ₆₄ ")
ROLL WEIGHT:	43.1 kg/roll (95 lb/roll)
Roll Area:	11.15 m² (120 ft²)
ROLLS/PALLET:	20

TECHNICAL DATA

Type A Hardness (ASTM D2240):

40 durometer

Temperature Stability: $-40^{\circ}\text{C to} +115^{\circ}\text{C} (-40^{\circ}\text{F to} +240^{\circ}\text{F})$

CONTACT US

For Your Project Specific Questions **Australia** +61 390187696 | **Middle East** +971 4 813 5501 | **UK** +44 203 9846444 **E.** info@pliteq.com.au



^{***} Trademarks of Pliteq Inc. The information provided is accurate to the best of our knowledge at the time of issue. However, we reserve the right to make changes when necessary without further notification. Suggested application may need to be modified to conform with local building codes and conditions. We cannot accept responsibility for products that are not used, or installed, to our specifications. All listed dimensions are nominal.

