

# GENIEMAT® RST02

## SOUND CONTROL UNDERLAYMENT



### PRODUCT SPECIFICATION

PRODUCT NAME:	GenieMat RST02
DIMENSION:	Rollgood: 1.2 m wide, 22.9 m long (4' wide, 75' long)
THICKNESS:	nom. 2 mm
DENSITY:	Shall be > 1000 kg/m <sup>3</sup> (62.3 lb/ft <sup>3</sup> )
ROLLS/PALLET:	16

### TECHNICAL DATA

NATURAL FREQUENCY	Shall not be greater than 92 Hz @ 19.2 kN/m <sup>2</sup> (400 psi) loading
BCA PART F5	Meets and exceeds on BCA part F5 impact performance requirements $\Delta L_{n,w}$ performance of 19 dB under LVT $\Delta L_{n,w}$ performance of 16 dB under ceramic tile
PUNCTURE TESTING WHEN INSTALLED UNDER LUXURY VINYL TILE: (ASTM F924)	No change when compared to puncture failure limit of luxury vinyl tile tested without underlayment
RESISTANCE TO IMPACT WHEN INSTALLED UNDER LUXURY VINYL TILE: (ASTM F1265)	Luxury vinyl tile shows no signs of breaking or cracking and meets standard criteria
ROLLING LOAD INDENTATION WHEN INSTALLED UNDER LUXURY VINYL TILE: (ASTM F2753)	Luxury vinyl tile shows no signs of indentation and plank separation for 12,500 cycles
TEMPERATURE STABILITY:	-40°C to +115°C (-40°F to +240°F)
ROBINSON WHEEL TEST WITH TILE (ASTM C627)	Achieves Extra Heavy Commercial

## CONTACT Us

For Your Project Specific Questions

**Australia** +61 390187696 | **Middle East** +971 4 813 5501 | **UK** +44 203 9846444

**E.** [info@pliteq.com.au](mailto:info@pliteq.com.au)

0621 © Pliteq Asia Pacific PTE LTD. 2021.

®/™ Trademarks of Pliteq Inc. The information provided is accurate to the best of our knowledge at the time of issue. However, we reserve the right to make changes when necessary without further notification. Suggested application may need to be modified to conform with local building codes and conditions. We cannot accept responsibility for products that are not used, or installed, to our specifications. All listed dimensions are nominal.



[www.pliteq.com.au](http://www.pliteq.com.au)