


TEST


Description & Application: A versatile and durable Rubber Floor – used for a wide range of market segments, including sport, fitness, schools, commercial spaces, and retail environments. **VersaTREAD** is made from recycled rubber content and coloured EPDM granules, crafted with precision and engineered for performance. **Pliteq** Floorings rubber is designed to meet the unique needs of each market, ensuring safety, comfort, and style for all.

| PHYSICAL SPECIFICATIONS | | | TECHNICAL SPECIFICATIONS | STANDARD | 3mm - 12mm |
|-------------------------|---|--|--------------------------|---------------|-------------------------|
| | FORMAT | ROLLS | SHORE HARDNESS | ASTM D2240 | >70 (<u>+</u> 5) |
| | DIMENSIONS THICKNESS SF/UNIT WEIGHT/ROLL | 1.2 m x 7.6 m 3 mm, 6 mm, 8 mm, 10 mm, 12mm 19.3 m ² 58 - 100.3 kg | COMPRESSION SET | ASTM D395 | -15 to -45% @25% |
| | | | TABER ABRASION | ASTM C501 | 0.45 |
| | | | ABRASION RESISTANCE | ASTM D3389 | 0.11g, 300 cycles |
| | | | WEAR INDEX | ASTM D3389 | 0.386 |
| | | | TENSILE STRENGTH | ASTM D412 | >2.1 MPa |
| | FORMAT DIMENSIONS THICKNESS SF/UNIT | TILE 0.6m x 0.6m or 1 m x 1 m 6mm, 8 mm, 9 mm 0.4m ² or 1.1 m ² | ELONGATION AT BREAK | ASTM D412 | >90% |
| | | | COEFFICIENT OF FRICTION | ASTM D1894-95 | Wet 1.20 / Dry 1.20 |
| | | | DENSITY | ASTM D792 | >1000 kg/m ³ |
| | | | CRITICAL RADIANT FLUX | | Test Reports |
| | FORMAT DIMENSIONS THICKNESS SF/UNIT | SHEET 1.2 m x 1.8 m 10 mm, 12 mm 2.2 m ² | AND MAXIMUM SMOKE | AS ISO 9239.1 | available upon |
| | | | DEVELOPMENT | | request |
| | | | TEAR | ASTM D624 | 9950 N/mm |
| | | | CHEMICAL RESISTANCE | ASTM F925-02 | No Change |
| | | | IGNITION CHARACTERISTICS | ASTM D2859 | Pass |


STANDARD COLOR OPTIONS



1710 GAMETIME GREEN



1714 REBOUND RED



1711 WILDCARD WHITE




1715 OVERTIME ORANGE



1712 STERLING SILVER



1716 COACH CORK



1713 BREAKAWAY BLUE



1717 BOLD BLACK

Warranty: Pliteq Flooring warrants that VersaTREAD, when installed according to its recommended procedures and adhesives, will be free from manufacturing defects. For more information, please review the Limited Lifetime Warranty document or contact your local Pliteq representative.











VersaTREAD


PREMIUM COLOR OPTIONS



1701 MULCH



1702 SANDSTONE



1703 OBSIDIAN



1704 GRANITE



1705 CONCRETE



1706 MARBLE

Additional Colors available, MOQ may apply.

