GENIEMAT® RST15 ROLL-OUT SOUND CONTROL UNDERLAYMENT



| PRODUCT SPECIFICATIONS | |
|--|--|
| PRODUCT NAME: | GenieMat RST15 |
| DIMENSION: | Roll: 1.22 m wide, 3.05 m long (4' wide, 10' long) |
| THICKNESS: | nom. 15 mm (5/8'") |
| WEIGHT: | 54.4 kg/Roll (120 lb/Roll) |
| AREA: | 3.72 m² (40 ft²) |
| DENSITY: | Shall be > 1000 kg/m^3 (62.43 lb/ft ³) |
| TECHNICAL DATA | |
| REDUCTION OF IMPACT SOUND PRESSURE LEVEL (ISO 10140): | Lnw 50dB when tested on a 200 mm concrete slab with vinyl Lnw 51dB when tested on a 200 mm concrete slab with wood |
| BUILDING CODE: | Meets and improves on Approved Document E impact performance requirements by 11 dB when used under LVT or hardwood flooring. |
| | Meets and exceeds on BCA part F5 impact performance requirements |
| POINT LOAD TEST FOR CRACK ISOLATION MEMBRANES (ANSI 118.12): | Exceeds pass criteria |
| PUNCTURE TESTING WHEN INSTALLED UNDER LUXURY VINYL TILE (ASTM F924): | No change when compared to puncture failure limit of luxury vinyl tile tested without underlayment |
| RESISTANCE TO IMPACT WHEN INSTALLED UNDER LUXURY VINYL TILE (ASTM F1265): | Luxury vinyl tile shows no signs of breaking of cracking and meets standard criteria |
| ROLLING LOAD INDENTATION WHEN INSTALLED UNDER LUXURY VINYL TILE (ASTM F2753): | Luxury vinyl tile shows no signs of indentation and plank separation for 12,500 cycles |
| VOC EMISSIONS (CDPH/ EHLB STANDARD METHOD v1.2-2017): | FloorScore [®] certified |

GENIEMAT® RST15 ROLL-OUT SOUND CONTROL UNDERLAYMENT



TECHNICAL DATA

TEMPERATURE STABILITY: -40° F to $+240^{\circ}$ F (-40° C to $+115^{\circ}$ C)

THERMAL TRANSMITTANCE (R-VALUE): 0.113 (m2K)/W

THERMAL TRANSMITTANCE

(U-VALUE):

 $8.8~W/m^2\cdot K$ (1.56 BTU/ $hr\cdot {}^{\circ}F\cdot ft^2$)

ROBINSON WHEEL TILE TEST

(ASTM C627):

Light commercial with tile





PLITEQ INC.

131 Royal Group Crescent Vaughan, ON L4H 1X9 Canada

4211, Yonge Street, Suite 404, Toronto, ON M2P 2A9 Canada

2015 Main St, Vancouver, BC V5T 3C2 Canada

T.+1 416 449 0049 info@pliteq.com www.pliteg.com

PLITEQ (DE)

251 Little Falls Drive Wilmington, DE 19808 United States of America

PLITEQ (AZ)

11701 N. 132nd Drive Surprise, AZ 85379 United States of America

T.+1 480 805 5560 info@pliteq.com www.pliteq.com

PLITEQ (UK) LTD.

Office 205, Orega High Holborn, 16 High Holborn, London, WC1V 6BX United Kingdom

T.+44 203 9846444 info@pliteq.co.uk www.pliteq.co.uk

PLITEQ MEXICO

Calz. Gral. Mariano
Escobedo 476-piso 12
Chapultepec Morales,
Anzures,
Miguel Hidalgo, 11590
Ciudad de México, CDMX
Mexico

T.+52 1 938 164 1551

PLITEQ ASIA PACIFC PTE LTD.

#19-13, 101 Cecil Street, Tong Eng Building, 069533 Singapore

T.+65 6813 2017 info@pliteq.sg www.pliteq.sg

PLITEQ BUILDING MATERIALS TRADING LLC.

European Business Centre Dubai Investment Park PO Box 473 512 United Arab Emirates

T. +971 4 567 4944 info@pliteq.ae www.pliteq.ae

PLITEQ AUSTRALIA PTY LTD.

68-82 York St, South Melbourne, VIC, 3205 Australia ABN: 86 675 027 433

T.+61 455 203 269 info@pliteq.com.au

www.pliteq.com.au



































